

Modular backup system for the field backup of HD, 2K and 4K
NEXTO STORAGE BRIDGE **NSB-25**



Components

	<p>Power Adapter (12V/2A)</p> <p>Built-in battery can be recharged by connecting the power adapter to the “6V~25V” port at the left of NSB-25. It takes about 5 hours to fully charge the battery, and a power adapter is required if you are connecting an external USB drive to NSB-25.</p>
	<p>USB 3.0 Cable</p> <p>USB 3.0 cable can be used to connect to a computer using the “COMPUTER” port at the left of NSB-25 or it can be used to connect to an external USB 3.0 drive using the “Ext. HDD” port.</p>
	<p>Shock protective rubber jacket</p> <p>Attach it to the left and right of NSB-25 to minimize the damage, should a drop/freefall occur.</p>
	<p>Hand strap</p> <p>Hand strap is designed for NSB-25, allowing you comfortable and long lasting.</p>
	<p>Stopper</p> <p>NSB-25의 삼각대 나사 구멍에 스톱퍼 (Stopper)를 장착하여 LCD 화면을 사용자가 보기 편한 각도로 맞춰 동영상 재생 등을 편안하게 확인 할 수 있습니다.</p>

Sold separately

	<p>D-tap cable</p> <p>D-tap cable is used to provide power from professional camera battery (which equipped with D-tap connector) to NSB-25.</p>
--	---

Sampler Pack (Sold separately)



Bridge Pellet
(Hard drive (or SSD) protection rubber filler, mini screwdriver and screw set, Rubber cover jacket)

NSB-25 includes 2 slots for 2 bridge pellets which can hold 2.5 inches SATA Hard drive (or SSD). The user puts the hard driver (or SSD) in the brige pellet by oneself, there is no limitation of capacity of hard drive (or SSD), but the limit of the height is 9.5mm.



Bridge Memory Module

The bridge pellet and memory card module are interchangeable for user's requirement.

Type 1	SxS / XQD / express P2
Type 2	RED / CFast / AJA PAK / 2.5" SATA drive
Type 3	P2
Type 4	AXSM
Type 5	RED MINI-MAG