

Pro-quality Field Backup Storage Device at a Competitive Price

NEXTO VIDEO STORAGE Doc **NVS2801**



Technical Specifications

Model Name	NEXTO VIDEO STORAGE Doc	
Model Number	NVS2801	
LCD	2.4" Color TFT LCD: 320*240, 64K color	
Memory Support	Built in slot	SxS(Pro/Pro+/-1), CFast(1.1&2.0), SD(SDHC/SDXC with UHS support)
Storage	Internal drive	2.5" SATA hard drive with 9.5mm and less height.
File System	Memory card	FAT16/32, exFAT, UDF, HFS+
	USB external drive	exFAT
Video Preview	DV, DVCPRO HD AVCHD, H.264, AVC-Intra MPEG2 4:4:4 / 4:2:2 / 4:2:0	XAVC 2K/4K, AVC Ultra 2K/4K XF-AVC 2K/4K, PRORES 2K/4K DNxHD 2K
	*Preview of 4K footage could be very slow.	
Photo Preview	EXIF JPEG file (.jpg) Canon RAW file (.cr2) FujiFilm RAW file (.raf) Leica RAW file (.dng / .rwl) Nikon RAW file (.nef)	Olympus RAW file (.orf) Panasonic RAW file (.rw2) Pentax RAW file (.dng / pef) Samsung RAW file (.srw) Sony RAW file (.arw)
	Rechargeable Li-Poly battery, 3.7V 4400mAH Operating time after full charge : 120min Rechargeable via AC adapter(5hrs), USB cable(9hrs)	
Computer I/F	USB 3.0 : 5Gbit/sec	
OS Compatibility	Windows XP(SP2) / VISTA / 7 / 8 / 10 (Windows XP requires exFAT patch update) MAC OS 10.6.5 or later, Linux 2.4.18 or later	
Power	Recommended : DC 12V/2A Operational range : DC 6~25V \pm 5% Operated by USB bus power during the computer connection	
Weight	430g / 0.95lb (with hard drive)	
Dimension	154 x 91 x 33 (mm) / 6 x 3.6 x 1.3 (inches)	
Contents	NVS2801 main unit / AC power adapter / USB3.0 cable / Rubber bumpers / Manual	